



**Tripp Lite**  
 1111 West 35th Street  
 Chicago, IL 60609 USA  
 Telephone: +(773) 869 1234  
 E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: P606-006-R

### Computer Cable, 6-ft. IEEE 1284 AB Parallel Gold Cable Cen36M to DB25M

#### Highlights

- Superior molded cables with integral strain relief and foil-shielding for maximum EMI/RFI protection
- IEEE 1284 cables' gold-plated connectors provide superior conductivity and support high-speed bi-directional printing
- Retail packaging



#### Description

Tripp Lite's 6-ft. IEEE 1284 A-B gold parallel printer cable connects computers with a DB25 female parallel port to parallel printers with a Centronics 36 female parallel port. It supports high-speed IEEE 1284 bi-directional communication. The cable features gold plated DB25 male/Cent36 male connectors and gold plated copper contacts for superior conductivity. It is manufactured from superior molded cable with integral strain relief and double shielding for maximum EMI/RFI protection. It contains low-capacitance, impedance matched, twisted-pair conductors that protect against cross-talk and other transmission problems. Tripp Lite warrants this product to be free from defects in materials and workmanship for life. Clamshell retail package.

#### System Requirements

- Computers with a DB25 Female parallel port
- Parallel printers with a Centronics 36 Female parallel port with high-speed IEEE 1284 Bi-Directional communication (although not essential).

#### Package Includes



- 6-ft. IEEE 1284 AB Parallel Gold Cable DB25M to Cen36M

#### Features

- Supports high-speed IEEE 1284 bi-directional communication (modes: standard compatible nibble byte ECP and EPP)
- Length: 6-ft. Connectors: DB25 male/Cent36 male
- Gold plated connectors and gold plated copper contacts offer superior conductivity
- Superior molded cable with integral strain relief and double shielding (foil and braid) for maximum EMI/RFI protection
- Low-capacitance impedance matched twisted-pair conductors protect against cross-talk and other transmission problems
- Bi-directional communication allows your printer to broadcast printer error messages back to network computers
- Molded ends with easy-grip textured overmold
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

#### Specifications

<b>PHYSICAL</b>	
Length	6 ft.
<b>CONNECTIONS</b>	

Connector A	 DB25 (MALE)
Connector B	 CENTRONICS 36 (MALE)

## Related Items

<b>Computer Cables</b>		
P606-003	Computer Cable, 3-ft. IEEE 1284 AB Parallel Gold Cable Cen36M to DB25M	Qty: [optional]
P606-010	Computer Cable, 10-ft. IEEE 1284 AB Parallel Gold Cable Cen36M to DB25M	Qty: [optional]

<b>Surge Protectors</b>		
DB25-PAR	Network Surge Suppressor - Essential protection for data and communication lines	Qty: [optional]

<b>Switches</b>		
B105-002-R	Switch - 2 Position Manual Data Switch	Qty: [optional]
B105-004-R	Switch - 4 Position Manual Data Switch	Qty: [optional]
B170-002-R	Switch - Reversible 2 Position IEEE Autoswitch	Qty: [optional]
B170-004-R	Switch - Reversible 4 Position IEEE Autoswitch	Qty: [optional]

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=2291](http://www.tripplite.com/en/products/model.cfm?txtModelID=2291).